

	Test report	148-QL22-R11 ver. 0	 <small>LAB N° 1235 L</small> <small>Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC</small> <small>Signatory of EA, IAF and ILAC Mutual Recognition Agreements</small>
	Applicant	Neri Spa Via Emilia, 1622 47020 - Longiano (FC) - Italy	
	Type	LULYR 32 cl I	

TEST REPORT 148-QL22-R11 ver. 0

Dates and authorization Date e autorizzazioni		
Report Date Data emissione rapporto di prova	12/04/2022	
Written by Preparato da	Matteo Roncali	
Authorized by Autorizzato da	Ing. Michele Peschiera	
Data declared under the sole responsibility of the applicant Dati dichiarati dal richiedente e sotto la sua responsabilità		
Applicant Richiedente	Neri Spa - Via Emilia, 1622 - 47020 - Longiano (FC) - Italy	
Manufacturer Produttore	Neri Spa - Via delle Querce, 4 - 47020 - Longiano (FC) - Italy	
Sample description Descrizione dispositivo	LED luminaire/ Apparecchio di illuminazione a LED	
Type Modello	LULYR 32 cl I	
Light source Sorgente luminosa	N°32 Leds Lumileds L150-30705006000S0 - 3000 K	
Secondary optic Ottica secondaria:	Ledil strada 2x2 ME-WIDE1	
Power supply Alimentazione	AC 230 V, 50 Hz	
Driver model Modello alimentatore	Philips Xi FP 75 W 0,3-1,05 A SNLDAE 230 V C133 sXt	
Output power supply current Corrente in uscita dall'alimentatore	830 mA	
Single led supply current Corrente sul singolo led	415 mA	
LM80 test report	CSA LM-80 test report number: LUMI012-A2-181 REV 1, 20-05-21 (accreditation NVLAP 500055-0)	
Applicable standards Norme applicabili		
	IES LM-82-12, UL 1598:2021, IES TM-21-11	

The test results and observations indicated in this test report refer exclusively to the samples as received and tested. It is not permitted to transfer the results to other systems or configurations. The publication or duplication of this test report with enclosures, or part of this test report or enclosures, without a written consent of the test laboratory is not permitted. The test laboratory not assumes any liability to any party for any loss, expense or damage occasioned by the use of this report. Any use of the laboratories name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by the test laboratory. In case of a multilingual test report, the English version is the only official version.

I risultati e le osservazioni indicate in questo rapporto di prova sono riferiti esclusivamente ai campioni così come ricevuti e testati. Non è permesso utilizzare i risultati e le osservazioni di questo rapporto di prova per altri sistemi o configurazioni. Non è permessa la pubblicazione o la duplicazione completa o parziale di questo rapporto di prova e dei suoi allegati senza un consenso scritto da parte del laboratorio di prova. Il laboratorio di prova non si assume responsabilità nei confronti di terzi per danni o eventuali costi derivanti dall'utilizzo dei dati presenti in questo rapporto di prova. Ogni uso del nome del laboratorio di prova e dei suoi marchi per la vendita o per pubblicizzare il prodotto testato deve essere prima approvato in forma scritta dal laboratorio di prova. In caso di rapporto di prova con più lingue, la versione inglese è da considerarsi quella ufficiale.

	Test report	148-QL22-R11 ver. 0	 <small>LAB N° 1235 L</small> <small>Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC</small> <small>Signatory of EA, IAF and ILAC Mutual Recognition Agreements</small>
	Applicant	Neri Spa Via Emilia, 1622 47020 - Longiano (FC) - Italy	
	Type	LULYR 32 cl I	

Test Name Identificazione prova	Result Risultato
IES LM-79-19 Test result	See test report QUALILAB 148-QL22-R02
IES LM-82-12, UL 1598:2021 par 19.7 (ISTMT)	See annex I
IES TM-21-11 Energy Star TM21 Calculator Rev 06-18-2018 (from calculation)	See annex II

Uncertainty Incertezza	
Photometric parameter Parametri fotometrici	Luminous flux and intensity= 2,5 % Luminous efficacy= 2,8 % Flusso e intensità luminosa, Efficacia luminosa
Temperature measurement Misure di temperatura	$\pm 2,0$ °C
Electrical parameter Parametri elettrici	$P= 0,13$ % $V= 0,05$ % $I_{AC}= 0,28$ % $I_{DC}= 0,08$ % $PF= 0,15$ %
Statement Dichiarazione	The measured value (y) and the associated expanded uncertainty (U) represent the interval ($y \pm U$) which contains the value of the measured quantity with a probability of approximately 95 % and a coverage factor $k = 2$. Il valore misurato (y) e l'incertezza estesa associata (U) rappresentano l'intervallo ($y \pm U$) che contiene il valore della grandezza misurata con una probabilità di circa il 95 % e un fattore di copertura $k = 2$.



Test report	148-QL22-R11 ver. 0
Applicant	Neri Spa Via Emilia, 1622 47020 - Longiano (FC) - Italy
Type	LULYR 32 cl I

ACCREDIA
L'ENTE ITALIANO DI ACCREDITAMENTO

LAB N° 1235 L

Membro degli Accordi di Mutuo Riconoscimento
EA, IAF e ILAC
Signatory of EA, IAF and ILAC
Mutual Recognition Agreements


Photographs


Foto



	Test report	148-QL22-R11 ver. 0	 <small>LAB N° 1235 L</small> <small>Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC</small> <small>Signatory of EA, IAF and ILAC Mutual Recognition Agreements</small>
	Applicant	Neri Spa Via Emilia, 1622 47020 - Longiano (FC) - Italy	
	Type	LULYR 32 cl I	

ANNEX I Electrical And Photometric Properties As A Function Of Temperature

Standards	IES LM-82-12, UL 1598:2021 par 19.7 (ISTMT)
Sample number	148-QL22-S02
Place of testing	Qualilab Srl - Via Trento, 87 - 25020 - Capriano del Colle (BS) - Italy
Date of testing	From 07/03/2022 to 09/03/2022
Environmental conditions	-
Instruments	<p>Illuminance transmitter Delta OHM HD2021T QL-IN-203 Powermeter Hioki 3333 QL-IN-186 Datalogger HIOKI 8400/20LR QL-IN-096 Termocouple TERSID T HF-D-30-TT QL-IN-197 Thermal chamber QUALILAB QL-IN-196 AC power source Chroma 6415 QL-IN-011 Thermal imager camera TESTO 865 QL-IN-253</p>
Test procedure	<p>IES LM-82-12 §6 Directional measurement method used. T_b: according to applicant's request the air temperature of the chamber was taken $T_{d,1}$: driver temperature central power supply $T_{c,1}$: Led module (see figure) $T_{c,2}$: Led module (see figure) $T_{c,3}$: Led module (see figure)</p> <p>Temperature setup $T_{b,0} = 25,0 \text{ }^\circ\text{C}$ $T_{b,1} = T_{b,0} + 25 \text{ }^\circ\text{C} = 50,0 \text{ }^\circ\text{C}$ $T_{b,2} = T_{b,0} + 10 \text{ }^\circ\text{C} = 35,0 \text{ }^\circ\text{C}$</p> <p>According to applicant's requirement the test was performed on a luminaire Stabilization time at each temperature >5 h</p>  <p>Only for the evaluation of the hot point position - Temperature value not validated</p>



Test Measurement

$T_{b,x}$ [°C]	$T_{d,1}$ [°C]	$T_{c,1}$ [°C]	$T_{c,2}$ [°C]	$T_{c,3}$ [°C]	Flux [lm]	Input Power [W]	Input Voltage [V]	Input Current [A]	Luminous efficacy [lm/W]
25,0	66,5	58,2	56,0	56,9	10126	80,1	230,0	0,350	126
35,0	72,8	65,0	63,0	63,8	9814	79,7	230,0	0,349	123
50,0	82,1	75,1	73,0	73,9	9405	79,3	230,0	0,331	119

	Test report	148-QL22-R11 ver. 0	 <small>LAB N° 1235 L</small> <small>Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC</small> <small>Signatory of EA, IAF and ILAC Mutual Recognition Agreements</small>
	Applicant	Neri Spa Via Emilia, 1622 47020 - Longiano (FC) - Italy	
	Type	LULYR 32 cl I	

ANNEX II	IES TM-21-11
Standards	IES TM-21-11
Sample number	148-QL22-S02
Light source	N°32 Leds Lumileds L150-30705006000S0 - 3000 K
Single led supply current	415 mA
Test procedure	Energy Star TM21 Calculator Rev 06-18-2018
Statement	Calculation below based on test report CSA LM-80 test report number: LUMI012-A2-181 REV 1, 20-05-21 (accreditation NVLAP 500055-0) and measurement data from annex I
TM21 calculation	

LM-80 Test Inputs																								
Description of LED Light Source Tested (manufacturer, model, catalog number)	Test Data for 55°C Case Temperature		Test Data for 85°C Case Temperature		Test Data for 105°C Case Temperature																			
	Time (hours)	Lumen Maintenance (%)	Time (hours)	Lumen Maintenance (%)	Time (hours)	Lumen Maintenance (%)																		
N°32 Leds Lumileds L150-30705006000S0 - 3000K	1000	100,00%	1000	99,50%	1000	98,60%																		
	2000	99,90%	2000	99,20%	2000	98,00%																		
	3000	99,90%	3000	99,10%	3000	97,70%																		
	4000	99,80%	4000	98,80%	4000	97,30%																		
	5000	99,70%	5000	98,70%	5000	97,00%																		
	6000	99,60%	6000	98,50%	6000	96,70%																		
	7000	99,70%	7000	98,40%	7000	96,50%																		
	8000	99,70%	8000	98,30%	8000	96,40%																		
	9000	99,70%	9000	98,20%	9000	96,30%																		
	10000	99,70%	10000	98,20%	10000	96,30%																		
	11000	99,60%	11000	98,10%	11000	96,10%																		
	12000	99,60%	12000	98,00%	12000	95,90%																		
	13000	99,50%	13000	97,90%	13000	95,70%																		
	14000	99,50%	14000	97,90%	14000	95,60%																		
	15000	99,40%	15000	97,80%	15000	95,50%																		
	16000	99,20%	16000	97,80%	16000	95,20%																		
	17000	98,90%	17000	97,70%	17000	94,80%																		
<table border="1"> <thead> <tr> <th colspan="2">LM-80 Testing Details</th> </tr> </thead> <tbody> <tr> <td>Total number of units tested per case temperature</td> <td>24</td> </tr> <tr> <td>Number of failures:</td> <td>0</td> </tr> <tr> <td>Number of units measured:</td> <td>24</td> </tr> <tr> <td>Test duration (hours):</td> <td>17000</td> </tr> <tr> <td>Tested drive current (mA):</td> <td>500</td> </tr> <tr> <td>Tested case temperature 1 (T_c, °C):</td> <td>55</td> </tr> <tr> <td>Tested case temperature 2 (T_c, °C):</td> <td>85</td> </tr> <tr> <td>Tested case temperature 3 (T_c, °C):</td> <td>105</td> </tr> </tbody> </table>							LM-80 Testing Details		Total number of units tested per case temperature	24	Number of failures:	0	Number of units measured:	24	Test duration (hours):	17000	Tested drive current (mA):	500	Tested case temperature 1 (T _c , °C):	55	Tested case temperature 2 (T _c , °C):	85	Tested case temperature 3 (T _c , °C):	105
LM-80 Testing Details																								
Total number of units tested per case temperature	24																							
Number of failures:	0																							
Number of units measured:	24																							
Test duration (hours):	17000																							
Tested drive current (mA):	500																							
Tested case temperature 1 (T _c , °C):	55																							
Tested case temperature 2 (T _c , °C):	85																							
Tested case temperature 3 (T _c , °C):	105																							
<table border="1"> <thead> <tr> <th colspan="2">In-Situ Inputs</th> </tr> </thead> <tbody> <tr> <td>Drive current for each LED package/array/module (mA):</td> <td>415</td> </tr> <tr> <td>In-situ case temperature (T_c, °C):</td> <td>75,1</td> </tr> <tr> <td>Percentage of initial lumens to project to (e.g. for L₇₀, enter 70):</td> <td>90</td> </tr> </tbody> </table>							In-Situ Inputs		Drive current for each LED package/array/module (mA):	415	In-situ case temperature (T _c , °C):	75,1	Percentage of initial lumens to project to (e.g. for L ₇₀ , enter 70):	90										
In-Situ Inputs																								
Drive current for each LED package/array/module (mA):	415																							
In-situ case temperature (T _c , °C):	75,1																							
Percentage of initial lumens to project to (e.g. for L ₇₀ , enter 70):	90																							
<table border="1"> <thead> <tr> <th colspan="2">Results</th> </tr> </thead> <tbody> <tr> <td>Time (t) at which to estimate lumen maintenance (hours):</td> <td>100.000</td> </tr> <tr> <td>Lumen maintenance at time (t) (%):</td> <td>92,87%</td> </tr> <tr> <td>Reported L90 (hours):</td> <td>>102000</td> </tr> </tbody> </table>							Results		Time (t) at which to estimate lumen maintenance (hours):	100.000	Lumen maintenance at time (t) (%):	92,87%	Reported L90 (hours):	>102000										
Results																								
Time (t) at which to estimate lumen maintenance (hours):	100.000																							
Lumen maintenance at time (t) (%):	92,87%																							
Reported L90 (hours):	>102000																							

T_{b,1} (50 °C)